PRODUCT SHEET

SWEP B12


The large-port B12 delivers compact heat transfer solutions for applications with large flows. It is available with different plate patterns to fulfil various thermal duties across a wide range of fluid viscosities and densities. The B12 is an excellent choice for demanding steam and air dryer applications. It can be as a desuperheater in air conditioning and a CO2 suction gas heat exchanger in refrigeration.



Basic specifications

Maximum number of plates (NoP)	140	
Max flow	16.9 m³/h (74.41 gpm)	
Channel volume	0.063/0.063 dm³ (0.0022/0.0022 ft³)	
Material	316/316L stainless steel plates, copper brazing	
Weight excl. connections	1.12+(0.12*NoP) kg 2.47+(0.265*NoP) lb	
Max Particle Size (mm)	1	

Standard dimensions



#	MM	IN
Α	287	11.3
В	117	4.61
С	234	9.21
D	63	2.48
F	4,40+2,34*(NoP)	0.17+0.09 *(NoP)
G	6	0.24
R	22	0.87
E_1	27	1.06
E_2	45	1.77



Available connections



Threaded Connection Threaded Ultra High Victaulic Connection Solder Connection

Approved

Connection Plate


Combo Connection

O-Ring Connection


Weld Connection

*For specific dimensions, or information about other types of connections, please contact your SWEP sales representative.

PED Pressure / Temperature



UL Pressure / Temperature



Product Concept

The Brazed Plate Heat Exchanger (BPHE) is constructed as a plate package of corrugated channel plates with a filler material between each plate. During the vacuum brazing process, the filler material forms a brazed joint at every contact point between the plates, creating complex channels. The BPHE allows media at different temperatures to come into close proximity, separated only by channel plates that enable heat from one media to be transferred to the other with very high efficiency. The concept is similar to other plate and frame technology, but without the gaskets and frame parts.

3rd party Approvals

Most SWEP products are approved by below listed certification organizations: Europe, Pressure Equipment Directive (PED) America, Underwriters Laboratories Inc (UL) Japan, Kouatsu-Gas Hoan Kyoukai (KHK) Additionally SWEP holds approvals from a vast variety of other certification organizations. For more details please contact your local SWEP representative. SWEP reserves the right to make changes without prior notice.

Find product solution - SSP

With SWEP's unique SSP, the SWEP Software Package, you can do advanced heat transfer calculations yourself. It's also easy to choose connections and generate drawings of the complete product. If you would like advice, SWEP offers all the service and support you need. Several SWEP accessories are also available to fulfill additional needs.

Disclaimer

The information and recommendations in regards to the products are presented in good faith, however, SWEP makes no representations or warranties as to the completeness or accuracy of the information. Information is supplied upon the condition that the purchasers will make their own determination as to the products' suitability for their purposes prior to use. Purchasers should note that the properties of the products are both application and material selection dependent and that products containing stainless steel are still object to corrosion if used in unsuitable environments. Standard data is presented, product variants with different data may exist. Contact your SWEP sales representative for more details. SWEP may change any data without notice.

