
SWEP B20

This ULTRA-COMPACT single circuit product is targeting Heat pumps. Large ports and innovative plate design enables an effective operating range up to 20 kW. B20 is delivering 30% less water pressure drop and a tighter temperature approach compared to similar products on the market. SWEP's versatile H pressure products enable efficient heat exchange in applications requiring high pressures. It is optimized for high performance with the refrigerant R410A & R32.



Maximum number of plates (NoP)	140	
Max flow	9.7 m³/h (42.71 gpm)	
Channel volume	0.0313/0.0301 dm³ (0.0011/0.0011 ft³)	
Material	316 Stainless Steel Plates, Cover Plates in 304 Stainless Steel, Copper Brazing	
Weight excl. connections	1.04+(0.0706*NoP) kg 2.30+(0.156*NoP) lb	
Max Particle Size (mm)	0.6	



#	MIM	IN
Α	324	12.76
В	94	3.7
С	268.2	10.56
D	39	1.54
F	6+1.46*(NoP)	0.24+0.06 *(NoP)
G	5	0.2
Н	269.2	10.6
I	20.7	0.81
J	1	0.04
K	19.7	0.78
R	26	1.02
E_1	20	0.79





Threaded Connection Threaded Ultra High Solder Connection Approved

