
## **SWEP B8LAS**

The compact B8LAS is a product developed to combine the highest thermal performance with low pressure drop. With a plate geometry using that uses AsyMatrix® technology, the unit offers a high efficiency and versatile solutions for high- efficiency heat pumps and refrigeration applications.



Maximum number of plates (NoP)	70
Max flow	4 m³/h (17.61 gpm)
Channel volume	0.0204/0.024 dm³ (0.0007/0.0008 ft³)
Material	316/316L stainless steel plates, copper brazing
Weight excl. connections	0.84+(0.059*NoP) kg 1.85+(0.130*NoP) lb
Max Particle Size (mm)	0.6



A 317.7 12.51   B 76.2 3   C 278 10.94   D 40 1.57   F 4+1.32*(NoP) 0.16+0.05 *(NoP)   G 6.3 0.25   R 18 0.71   E_1 20 0.79   E_2 45 1.77	#	MM	IN
C 278 10.94   D 40 1.57   F 4+1.32*(NoP) 0.16+0.05 *(NoP)   G 6.3 0.25   R 18 0.71   E_1 20 0.79	Α	317.7	12.51
D 40 1.57   F 4+1.32*(NoP) 0.16+0.05 *(NoP)   G 6.3 0.25   R 18 0.71   E_1 20 0.79	В	76.2	3
F 4+1.32*(NoP) 0.16+0.05 *(NoP)   G 6.3 0.25   R 18 0.71   E_1 20 0.79	С	278	10.94
G 6.3 0.25   R 18 0.71   E_1 20 0.79	D	40	1.57
R 18 0.71 E_1 20 0.79	F	4+1.32*(NoP)	0.16+0.05 *(NoP)
<b>E_1</b> 20 0.79	G	6.3	0.25
_	R	18	0.71
<b>E_2</b> 45 1.77	E_1	20	0.79
	E_2	45	1.77





Threaded Connection Threaded Ultra High Solder Connection Combo Connection Approved

Hose Connection

Weld Connection

