
SWEP DBD500

The DB500 is a highly effective, versatile True Dual condenser which is the perfect choice for applications such as flexible chillers, industrial heat pumps, and modular compact reversible chillers. Its advantage is its ability to deliver full performance at both full and half load.



| Maximum number of plates (NoP) | 298 | |
|--------------------------------|---|--|
| Max flow | 83 m³/h (365.44 gpm) | |
| Channel volume | 0.539/0.547 dm³ (0.0190/0.0193 ft³) | |
| Material | 316/316L stainless steel plates, copper brazing | |
| Weight excl. connections | 12.00+(0.93*NoP) kg 26.45+(2.050*NoP) lb | |
| Max Particle Size (mm) | 1 | |



| # | MM | IN |
|-----|---------------|------------------|
| Α | 980 | 38.58 |
| В | 304 | 11.97 |
| С | 866 | 34.09 |
| D | 191 | 7.52 |
| F | 12+2.29*(NoP) | 0.47+0.09 *(NoP) |
| G | 6 | 0.24 |
| M | 836 | 32.91 |
| R | 44 | 1.73 |
| E_1 | 54 | 2.13 |
| E_2 | 27 | 1.06 |





Threaded Connection Victaulic Connection Solder Connection Flange Connection Weld Connection

