

# B285


The demand for natural refrigerants, such as CO<sub>2</sub>, is increasing. With pressure requirements for transcritical CO<sub>2</sub> applications touching 140 bar, the B285H is the natural choice. The B285H is optimized for high heat load capacities (up to 550 kW as a gas cooler, with flow capacity above 50 m<sup>3</sup>/h). The compact, yet lightweight, B285 is suitable for cold-chain applications, such as hypermarkets, supermarkets, and heat recovery. It also suitable for different heat pump applications.



## Basic specifications


Maximum number of plates (NoP)	126
Max flow	48.8 m <sup>3</sup> /h (214.86 gpm)
Channel volume	0.157/0.161 dm <sup>3</sup> (0.0055/0.0057 ft <sup>3</sup> )
Material	316/316L stainless steel plates, copper brazing
Weight excl. connections	17.30+(0.75*NoP) kg 38.14+(1.653*NoP) lb
Max Particle Size (mm)	0.8

## Standard dimensions



#	MM	IN
A	527.10	20.75
B	245.10	9.65
C	454	17.87
D	164	6.46
F	18,00+2,15*(NoP)	0.71+0.08*(NoP)
G	0	0
H	440	17.32
J	6	0.24
K	35.60	1.4
N	43.50	1.71
R	35	1.38
E_1	45	1.77


## Available connections



Threaded Ultra High Approved    Solder Connection    Weld Connection

\*For specific dimensions, or information about other types of connections, please contact your SWEP sales representative.

## PED Pressure / Temperature



## Product Concept

The Brazed Plate Heat Exchanger (BPHE) is constructed as a plate package of corrugated channel plates with a filler material between each plate. During the vacuum brazing process, the filler material forms a brazed joint at every contact point between the plates, creating complex channels. The BPHE allows media at different temperatures to come into close proximity, separated only by channel plates that enable heat from one media to be transferred to the other with very high efficiency. The concept is similar to other plate and frame technology, but without the gaskets and frame parts.

## 3rd party Approvals

Most SWEP products are approved by below listed certification organizations: Europe, Pressure Equipment Directive (PED) America, Underwriters Laboratories Inc (UL) Japan, Kouatsu-Gas Hoan Kyoukai (KHK) Additionally SWEP holds approvals from a vast variety of other certification organizations. For more details please contact your local SWEP representative. SWEP reserves the right to make changes without prior notice.

## Find product solution - SSP

With SWEP's unique SSP, the SWEP Software Package, you can do advanced heat transfer calculations yourself. It's also easy to choose connections and generate drawings of the complete product. If you would like advice, SWEP offers all the service and support you need. Several SWEP accessories are also available to fulfill additional needs.

## Disclaimer

The information and recommendations in regards to the products are presented in good faith, however, SWEP makes no representations or warranties as to the completeness or accuracy of the information. Information is supplied upon the condition that the purchasers will make their own determination as to the products' suitability for their purposes prior to use. Purchasers should note that the properties of the products are both application and material selection dependent and that products containing stainless steel are still object to corrosion if used in unsuitable environments. Standard data is presented, product variants with different data may exist. Contact your SWEP sales representative for more details. SWEP may change any data without notice.