


# BX4T


The BX4T enables a new level of efficient heat exchange, with the X-plates on front and back that give structural stability while being active heat transfer plates. This All-Active plate pack maximizes the material utilization and makes the product an efficient and competitive product for demanding applications and narrow temperature approaches. Easy to install and use, the product is small yet flexible, which makes it a particularly good choice for economizer applications focusing on VRF and heat pumps. The BX4T's mechanical design makes it suitable for high pressure refrigerants such as R410A and R32.



## Basic specifications

Maximum number of plates (NoP)	100
Max flow	1.2 m <sup>3</sup> /h (5.28 gpm)
Channel volume	0.0093/0.0093 dm <sup>3</sup> (0.0003/0.0003 ft <sup>3</sup> )
Material	304 stainless steel plates, copper brazing
Weight excl. connections	0.26+(0.0405*NoP) kg 0.58+(0.089*NoP) lb

## Standard dimensions



#	MM	IN
A	192.60	7.58
B	75	2.95
C	154	6.06
D	40	1.57
F	2.00+(1.06*(NoP-2.00))	0.08+(0.04*(NoP-0.08))
G	6	0.24
R	18	0.71
E_1	20	0.79


## Available connections



Threaded Connection Solder Connection Combo Connection Hose Connection

\*For specific dimensions, or information about other types of connections, please contact your SWEP sales representative.

## PED Pressure / Temperature



## UL Pressure / Temperature



## Product concept

The Braze Plate Heat Exchanger (BPHE) is constructed as a plate package of corrugated channel plates with a filler material between each plate. During the vacuum brazing process, the filler material forms a brazed joint at every contact point between the plates, creating complex channels. The BPHE allows media at different temperatures to come into close proximity, separated only by channel plates that enable heat from one media to be transferred to the other with very high efficiency. The concept is similar to other plate and frame technology, but without the gaskets and frame parts.

## 3rd party Approvals

Most SWEP products are approved by below listed certification organizations: Europe, Pressure Equipment Directive (PED) America, Underwriters Laboratories Inc (UL) Japan, Kouatsu-Gas Hoan Kyoukai (KHK) Additionally SWEP holds approvals from a vast variety of other certification organizations. For more details please contact your local SWEP representative. SWEP reserves the right to make changes without prior notice.

## Find product solution - SSP

With SWEP's unique SSP, the SWEP Software Package, you can do advanced heat transfer calculations yourself. It's also easy to choose connections and generate drawings of the complete product. If you would like advice, SWEP offers all the service and support you need. Several SWEP accessories are also available to fulfill additional needs.

## Disclaimer

The information and recommendations in regards to the products are presented in good faith, however, SWEP makes no representations or warranties as to the completeness or accuracy of the information. Information is supplied upon the condition that the purchasers will make their own determination as to the products' suitability for their purposes prior to use. Purchasers should note that the properties of the products are both application and material selection dependent and that products containing stainless steel are still object to corrosion if used in unsuitable environments. Standard data is presented, product variants with different data may exist. Contact your SWEP sales representative for more details. SWEP may change any data without notice.