


SWEP B4T, 0292485.0-Preconfig

Configuration number (CN) with sort key: 0292485.0-Preconfig

Denomination: B4THx40/1P-NC-U 4x3/4"&16

Number of plates (NoP): 40

Standard dimensions



#	MM	IN
A	194.50	7.66
B	76.90	3.03
C	154	6.06
D	40	1.57
F	50	1.98
G	4	0.16
R	18	0.71

Measurement (Tolerance)

Preliminary Tolerances

Connections

F = Front side connections, P = Back side connections


POSITION	ART. NO.	DENOMINATION	HEIGHT (E)	MATERIAL
F1, F2, F3, F4	32835	ISO-G 3/4" & SOLDER 16	20	Stainless Steel 316

Accessories


Not visible in sketch

ART. NO.	DENOMINATION
24002	4/4T STUD BOLT LOC.F 2xCV76.2 (M6x15 ONLY FOR DAIKIN)

PED Pressure / Temperature



UL Pressure / Temperature



Product Data

PED Category	SEP
Total weight, including connections	3.0 kg
Total Heat Transfer area	0.6 m ² (6.0 ft ²)
Hold up volume circuit 1	0.1767 dm ³ (0.006 ft ³)
Hold up volume circuit 2	0.186 dm ³ (0.007 ft ³)

MATERIALS

304 Stainless Steel Plates, Copper Brazing

Disclaimer

The information and recommendations in regards to the products are presented in good faith, however, SWEP makes no representations or warranties as to the completeness or accuracy of the information. Information is supplied upon the condition that the purchasers will make their own determination as to the products' suitability for their purposes prior to use. Purchasers should note that the properties of the products are both application and material selection dependent and that products containing stainless steel are still object to corrosion if used in unsuitable environments. Standard data is presented, product variants with different data may exist. Contact your SWEP sales representative for more details. SWEP may change any data without notice.